

Schall-Ex® Duo L-15/28 OS

DETAILS

| | |
|---------------|--|
| Articlenumber | 1-404 |
| Function | hinged door |
| Türenmaterial | timber, metal |
| Application | interior door |
| Usage | sound protection, smoke protection, fire protection, accessibility |

TECHNICAL DATA


| | |
|----------------------|------------------------------|
| Width | 14.8 mm |
| Height | 28 mm |
| Min. delivery length | 708 mm |
| Max. delivery length | 2000 mm |
| Standard length | 708, 833, 958, 1083, 1208 mm |
| max. travel | 12 mm |
| Actuation | double-sided |
| Actuator | actuator/ actuator |
| Outerprofile | aluminium |
| Surface | plate finish |
| Sealingprofile | silicone, self-extinguishing |

FITTING

| | |
|--------|---|
| Fixing | OS - omega-shaped profile unterschrauben |
|--------|---|

EXAMINATIONS AND CERTIFICATES

| | |
|--------------------------|-----|
| Permanent function IM | yes |
| Mio Certificate | yes |
| Leakage rate certificate | yes |
| Barrier free | yes |
| UL | yes |
| EPD | yes |
| Certifire | yes |





I-Ex[®] Duo L-15/28 OS



Schall-Ex[®] L-15/28 OS



Schall-Ex® Duo L-15/

